



DEDUCTIONS	
Load Block	See block manufacturer nameplate
Overhaul Ball	See overhaul ball manufacturer nameplate
Hose Reel	160 lb 72,57 kg
Swing Around Jib (Stowed)	See load rating chart

BOOM AND JIB COMBINATIONS			
1747C	47'	3-Section Boom	18' - 30' 2-Section Jib
1761C	61'	3 Section Boom	23' - 40' 2-Section Jib
1770C	70'	3-Section Boom	23' - 40' 2-Section Jib
1781C	81'	4-Section Boom	23' - 40' 2-Section Jib

ALLOWABLE LINE PULL				
1 Part Line	2 Part Line	3 Part Line	4 Part Line	WARNING
				Anti-two-block system must be in good operating condition before operating crane. Refer to the owner's manual. Keep at least three wraps of load line on the drum at all times.
8,500 lb 3 856 kg	17,000 lb 7 711 kg	25,500 lb 11 567 kg	34,000 lb 15 422 kg	
7,400 lb 3 357kg	14,800 lb 6 713 kg	22,200 lb 10 070 kg	29,600 lb 13 426 kg	.5625" ROTATION RESISTANT (5.0:1 SF) - 37000 lbs breaking strength



Manitex  
 3000 South Austin Avenue  
 P.O. Box 1609  
 Georgetown, TX, USA 78627-1609  
 Telephone 512-942-3000  
 Facsimile 512-863-3776  
 www.manitex.com

**UPTime is the Manitex commitment to complete support of thousands of units working every day.**



- Includes 24-7-365 parts shipments.
- Utilizes the efficiency of UPNet online parts order system.
- Relies on Manitex's UPTrak support tracking system for performance analysis and resource allocation.
- Features REMan, Manitex's cost effective rebuild/exchange program.
- Provides expert service technicians for troubleshooting and site visits.
- Mandates training; at our facility and yours. It includes coordinated support from all component suppliers.
- Involves every Manitex team member in the support of every Manitex customer.

### What does UPTime mean to Manitex customers?

**UPTime** means reliability.

**UPTime** means utilization.

**UPTime** means profitability.

MTX 1703 • 01.05 • TG • 3,000

# series 1703

## BOOM TRUCKS

## features

- 17 Ton (15,5 mton) Capacity
- 3-Section Proportional Booms 70' (21,3 m), 61' (18,6 m) and 47' (14,3 m)
- 4-Section 81' (24.7 m) Proportional Boom
- 131' 6" (40,1 m) Maximum Tip Height
- 2-Section, Telescopic Jibs 30' (9,1 m) and 40' (12,2 m)
- 2-Speed Layaway Planetary Hoist with Grooved Drum and Negative Draft Flange
- Radio ATB
- Removable Boom Rest
- Hydraulic Capacity Alert Warning System (HYCAS) - with Shutdown
- Optional Load Moment Indicator with Digital Display, CAN Bus, Overload Shutdown and Internal Boom Length Cable
- 20' 10" A-Frame Outriggers
- 10' A-Frame Rear Stabilizers
- Optional Front Bumper Stabilizer with Auto Retract Feature for 360° Area of Operation
- System Pressure Gauge
- Clamp-On Mounting
- Rugged Weatherproof Connectorized Electrical System. Circuit Status LED when Equipped with LMI Option.
- Manitex UPTime Comprehensive Support



# product guide



0' (3,05m) of live power lines.  
 sult factory for other boom options.